



ELECTRICALLY CHARGED
POLYPROPYLENE



ClingZ® is an adhesive-free electrically charged film that adheres to any dry interior surface and is effortless to reposition.

ClingZ

Ideal for temporary indoor marketing applications

Effortless to apply, remove and reposition to any dry interior surface

Adhesive free – no glue, tape, tacks or pins required

Chemically inert, PVC-Free and phthalate-free

Can be die cut, kiss cut and plotter cut

Available in white and clear

Print Compatibility: Offset (Conventional and UV), HP Indigo and UV Wide Format*



This logo represents Nekoosa's commitment to offering sustainable alternatives to traditional PVC materials. 100% of this product line is PVC-Free.

Easy to apply and remove from these surfaces:



ClingZ is not to be confused with Static Cling Vinyl. Static Cling Vinyls cling to glass because of their high plasticizer content. **They do NOT cling by static.** Only ClingZ gets its cling properties due to having an embedded static charge.

Applications

- Screen Safe Labels
- In-Store Promotional Signage
- Large Format Graphics
- Tileable Murals
- P.O.P. Signage
- Reverse Sided Graphics
- Trade Show & Event Signage
- Window Graphics
- Holiday Décor & Decals
- Guerrilla Marketing

Certified for
HP Indigo



800.826.4886 | sales@nekoosa.com

NEKOOSA.COM

07.27.23 | M1386



ELECTRICALLY CHARGED
POLYPROPYLENE



STOCKED PRODUCTS ▶

	Color	SKU #	Size	GSM	M Wgt	Qty/Unit	
ClingZ Standard Offset							
White		➤ 71100	19" x 25"	240	162.2	2000/skid	
		➤ 71101	23" x 35"		274.8	2000/skid	
		➤ 71102	28" x 40"		382.4	2000/skid	
		➤ 71105	19" x 25"		162.2	200/carton	
		➤ 71106	23" x 35"		274.8	200/carton	
		➤ 71107	28" x 40"		382.4	200/carton	
		➤ 71110	19" x 25"		164.2	2000/skid	
Clear		➤ 71111	23" x 35"	243	278.3	2000/skid	
		➤ 71112	28" x 40"		387.2	2000/skid	
		➤ 71115	19" x 25"		164.2	200/carton	
		➤ 71116	23" x 35"		278.3	200/carton	
		➤ 71117	28" x 40"		387.2	200/carton	
ClingZ Versaliner Offset*							
White		➤ 71200	20" x 28"	243	193.6	2000/skid	
		➤ 71201	28" x 40"		387.2	2000/skid	
		➤ 71205	20" x 28"		193.6	250/carton	
		➤ 71206	28" x 40"		387.2	250/carton	
Clear		➤ 71210	20" x 28"	246	196.0	2000/skid	
		➤ 71211	28" x 40"		392.0	2000/skid	
		➤ 71215	20" x 28"		196.0	250/carton	
		➤ 71216	28" x 40"		392.0	250/carton	
ClingZ HP Indigo							
White		➤ 71300	12" x 18"	269	82.6	500/carton	
		➤ 71301	13" x 19"		94.5	500/carton	
		➤ 71310	20.5" x 29.5"		231.4	1200/skid	
		➤ 71312	20.5" x 29.5"		231.4	300/carton	
Clear		➤ 71305	12" x 18"	261	80.2	500/carton	
		➤ 71306	13" x 19"		91.7	500/carton	
		➤ 71311	20.5" x 29.5"		224.5	1200/skid	
		➤ 71313	20.5" x 29.5"		224.5	300/carton	
ClingZ Wide Format							
White		➤ 71514 ●	54" x 75'	161	12	1/Roll	
Clear		➤ 71515 ●	54" x 75'	155	12	1/Roll	

*Select ClingZ Versaliner if extra finishing like die or kiss cutting is required.





ELECTRICALLY CHARGED
POLYPROPYLENE

TECHNICAL DATA ▶

Physical Properties			Offset	Versaliner	HP Indigo	UV Wide Format	
Film	Polypropylene	Liner	10 pt paper	10 pt paper	10 pt paper	PET	
Color	White and Clear	Thickness	Film	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)
			Liner	10 mil (254 μ)	10 mil (254 μ)	10 mil (254 μ)	3 mil (76.2 μ)
			Film + Liner	12 mil (304.8 μ)	12 mil (304.8 μ)	12 mil (304.8 μ)	5 mil (127 μ)

Conditions for Use			Offset	Versaliner	HP Indigo	UV Wide Format
Shelf Life	1 year	Application Time	6 months	6 months	3 months	3 months
Min. Application Temp.	32° F (0° C)					
Service Temp. Range	0° F to 105° F (-17.8° C to 40.5° C)					
Outdoor Durability	None					



General Printing and Designing Guidelines:

- Design for finished sizes of at least 3"x5" (8x12 cm).
- Convert PMS spot colors to CMYK process-ink builds.
- Stay within a total area coverage (TAC) of 220% in color build with a line screen of 150-175, and reduce screen values by using UCR or GCR.
- Avoid heavy deposits of ink near the edge to avoid curling.
- Right reading or reverse printing is possible.
- A 1" (2.5 cm) unprinted border will enhance the performance of the application.
- Add no more than 2 hits of opaque white before 4-color process when printing on clear film.
- Add white after the 4-color process if printing verse.
- This product is not suitable for screen printing or any type of coating, including varnishes or aqueous and UV coatings.

Storing:

- Store in the original packaging at room temperature 65° F-80° F (18° C-27° C) with relative humidity of 25-50%.
- Acclimate the material to press room temperature for 24 hours prior to printing.
- Remove material from plastic bag right before the loading the press.
- Reseal unused materials in the original plastic bag.
- Paper liner is moisture sensitive and can curl if improperly stored.
- Unprinted ClingZ can be stored for up to one year.

Additional Information:

- ClingZ is not to be confused with static cling vinyl. Static cling vinyls adhere to glass because of their high plasticizer content. They do not cling by static. Only ClingZ gets its cling properties due to having an embedded static charge.
- ClingZ is recyclable as a #5 plastic. Confirm specific recycling guidelines with your local municipality.

Certified for
HP Indigo

HP CERTIFIED:
ClingZ for HP Indigo Clear 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900
ClingZ for HP Indigo White 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.